

Fortsetzung von vorheriger Seite

**EH 22700.**

Best.-Nr. Stahl, vergütet	Best.-Nr. Rostfreier Stahl	Ausführung	d <sub>1</sub>	l <sub>2</sub>	d <sub>3</sub>	Kugel	SW	Belastbarkeit bei statischer Belastung max. kN*	g
22700.0772	–	abgeflachte Kugel,	<b>M 20</b>	<b>30</b>	13,5	15,0	10	60	51,0
22700.0774	–	Auflagefläche geriffelt	<b>M 20</b>	<b>40</b>	13,5	15,0	10	60	69,0
22700.0775	–		<b>M 20</b>	<b>50</b>	13,5	15,0	10	60	90,0
22700.0776	–		<b>M 20</b>	<b>60</b>	13,5	15,0	10	60	110,0
22700.0782	–		<b>M 24</b>	<b>35</b>	15,8	18,0	12	80	84,0
22700.0784	–		<b>M 24</b>	<b>50</b>	15,8	18,0	12	80	128,0
22700.0786	–		<b>M 24</b>	<b>80</b>	15,8	18,0	12	80	215,0

\* Belastbarkeitsangaben gelten nicht für Ausführung aus rostfreiem Stahl.

## Kugeldruckschrauben

ohne Kopf,  
Kugel  
verdrehgesichert

