



## Wartungsfreie Führungsbuchsen

Form B ohne Zentrieransatz

Mehrstoffbronze mit Festschmierstoffeinsätzen

Bohrung  $d_1$  ISO Toleranz H7  
 Außen-Ø  $d_2$  ISO Toleranz k6  
 Zentrieransatz  $d_2$  ISO Toleranz e7



Nr. 08 158

Bestellbeispiel

08158.14.00X36

Form B  
 d 1 14  
 s 1 36



$d_1^{H7}$	$s_1^{-0,5}_{-1}$	$d_{2k6}$	$d_3$	k	$d_4$	$l_2$
9 + 10	12	14	16	3		
	17					
	22					
	27					
	36					
	46				$d_1 + 0,5$	15
	56				$d_1 + 0,5$	15
14 + 15	17	20	25	6		
	22					
	27					
	36					
	46				$d_1 + 0,5$	10
	56				$d_1 + 0,5$	10
	66				$d_1 + 0,5$	15
	76				$d_1 + 0,5$	15
18 + 20	17	26	31	6		
	22					
	27					
	36					
	46					
	56					
	66				$d_1 + 0,5$	10
	76				$d_1 + 0,5$	10
	86				$d_1 + 0,5$	20
	96				$d_1 + 0,5$	20
22 + 24	17	30	35	6		
	22					
	27					
	36					
	46					
	56					
	66					
	76				$d_1 + 0,5$	10
	86				$d_1 + 0,5$	10
	96				$d_1 + 0,5$	20
	116				$d_1 + 0,5$	20
30 + 32	27	42	47			
	36					
	46					
	56					
	66					
	76					
	86					
	96				$d_1 + 0,5$	10
	116				$d_1 + 0,5$	20
	136				$d_1 + 0,5$	30
40 + 42	56	54	60	10		
	66					
	76					
	86					
	96					
	116				$d_1 + 0,5$	25
	136				$d_1 + 0,5$	35
	156				$d_1 + 0,5$	45
	196				$d_1 + 0,5$	60

08